



Shell side baffling develops good CW side turbulence for max cooling and cooler surface temperatures for long life. Long counterflow coil nets maximum delta T

ED REED COMPANY

713.432.0519
www.Edreed.com
Ben@Edreed.com

NOTE:

THIS DOCUMENT IS CONFIDENTIAL, AND CONTAINS INFORMATION WHICH IS PROPRIETARY TO SEC. IT IS PROVIDED IN CONFIDENCE AND UPON THE CONDITION THAT NEITHER IT NOR THE INFORMATION CONTAINED IN IT WILL BE COPIED, DISCLOSED, OR USED IN WHOLE OR IN PART WITHOUT THE PRIOR WRITTEN CONSENT OF SEC.

ARROWS DENOTE PATH OF COOLING WATER FLOW

COOLING WATER INLET 3/4" FNPT

slotted

SHEET 1 OF 1

REVISIONS

TOLERANCES ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED

FRACTIONAL	±	INCH.
DECIMAL	±	INCH.
ANGULAR	±	DEG.
HOLE LOC.	±	INCH.

SENTRY EQUIPMENT CORP.
856 EAST ARMOUR ROAD, OCONOMOWOC WI 53066

TR and FR series flow path

FILENAME	01212A01	DATE	02/19/94	DRAWN	TJS	CKD	APPD
SCALE	1=2	DWG. NO.	10-01212A-1		REVISION	0	